

High Efficiency Replacement Elements

UL Elements 12 - 2370 m³/hr Flow Range

Features

- Pleated media for high dirt holding capacity
- Heavy duty industrial strength glass surrounded by galvanized expanded metal
- Sized to minimize pressure drop
- Plastisol potting standard

Technical Specifications

- 99.995% removal efficiency to 0.1 micron
- Temp (continuous): min -26°C (-15°F), max 104°C (220°F)

Options

- Chemical resistant and high temperature construction

Applications


- Medical / Pharmaceutical industry

Endcap Construction

- B = Closed one end with bolt hole, open on other end
- C = Closed one end, open on other end
- G = Galvanized metal
- M = Molded plastisol
- N = Neoprene blended gasket on open endcaps
- R = Mixed rubber/cork gasket on open endcaps



UL Elements 12 - 2370 m³/hr Flow Range



Element Part Number	Element m ³ /h Rating	Dimensions - mm			Std. Endcap Features
		I.D.	O.D.	H.T.	
JUL10	18	--	102	35	--
JUL14	15	76	111	59	M
JUL18	37	76	111	121	M
JUL30	95	92	146	121	M
JUL34	161	121	200	122	M
JUL230	190	92	146	241	M
JUL234	352	121	200	244	GN
JUL238	558	124	235	254	GN
JUL244	587	152	248	244	GN
JUL274	734	203	298	244	GN
JUL334	547	121	200	368	GN
JUL344	866	152	248	368	GN
JUL374	1092	203	298	368	GN
JUL376	1974	229	371	368	GN
JUL384	2370	356	498	368	GN

800 Series Elements

Element Part Number	Element m ³ /h Rating	Dimensions - mm			Std. Endcap Features
		I.D.	O.D.	H.T.	
JUL824	12	38	64	68	GC
JUL842	24	60	98	70	G
JUL848	73	65	127	121	G
JUL850	219	89	149	222	GR
JUL850/1	219	89	149	222	GBR
JUL896	82	60	101	214	GB

See Element Technical Data for maintenance guidelines.